

XEROX FLOOR GRAPHIX ADHESIVE COMPATIBILITY



Internal Surface	Duration	Peelability	Comments
Polished Concrete	Up to 2 years	Clean	Cleanliness of peel can be affected by cleanliness of surface before application. Hot water & Detergent, or Alcohol can remove residues
Painted Concrete	Up to 3 months*	Clean*	* Highly dependant on paint system used and integrity. We recommend customer testing discrete area first.
Sealed Tiles	Up to 1 year	Clean	Cleanliness of peel can be affected by cleanliness of surface before application. Hot water & Detergent, or Alcohol can remove residues.
Resin Flooring -Supermarket / Retail type	Up to 1 year	Clean	Cleanliness of peel can be affected by cleanliness of surface before application. Hot water & Detergent, or Alcohol can remove residues
Laminate Flooring	Up to 1 year	Clean	Cleanliness of peel can be affected by cleanliness of surface before application. Hot water & Detergent, or Alcohol can remove residues
Short-pile Carpet	Up to 3 years	Clean	
Parquet Flooring	Up to 6 months*	Clean*	* Highly dependant on varnishing system used. We recommend customer testing discrete area first
Porous Concrete			Not recommended
Porous Tiles			Not recommended
Marble Flooring			Not recommended
Linoeum / PVC Flooring			Not recommended
Long-pile Carpet			Not recommended
Indoor Sports Courts			Not recommended

NOTE: Surface cleanliness, foot-fall, cleaning agent choice and environment can influence the durability of the adhesive and its ability to bond and peel cleanly from a given surface. The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted.. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.

