

MATERIAL DESCRIPTION

Coala Dry Erase Lam is a 40 mic gloss finish biaxially-Oriented polypropylene laminating film. Coated on one side with aqueous acrylic adhesive. Protected by a bleached Kraft release paper coated on one side with a siliconised polyethylene. Ideally suited for application to heat-sensitive output and high ink coverage prints printed on photo gloss paper.

FILM THICKNESS



PRODUCT STRUCTURE

- Support: 40 mic gloss polypropylene
- Adhesive: 25 mic Aqueous Acrylic
- Liner: One side siliconised polyester
- UV Protection Factor: Adhesive contain UV stabilisers, which prevent film degradation and provides UV protection to the underlying image.
- Outdoor durability: Up to 2 years
- Peel Strength (20 min, FTM1): 11N/25mm
- Heat Resistance Range: 110 to 120°C

RECOMMENDATIONS

- Recommended settings for Roller Laminator :
Temperature 49°C, speed 0.3m to 2.5m per minute

APPLICATIONS

- Dry-erase presentation boards
- Schedules
- Year planners
- Maps

**PVC
FREE**

SHELF LIFE STORAGE AND CONDITIONS



- Store in closed original packaging in a cool, dry environment 10-25°C with 50% relative humidity.
- Shelf life of one year if stored in original packaging in recommended conditions.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

