

MATERIAL DESCRIPTION

Coala Folio Cling is a 150 μ white and clear gloss cling monomeric soft-PVC vinyl used for screenprint, UV-Offset or UV inkjet.

PRINTER & INK COMPATIBILITY



THICKNESS

150 μ

PHYSICAL PROPERTIES

Face material: White and clear monomeric vinyl

- Caliper: 150 $\pm$ 3%
- Surface tension : 34 dyne/cm

Liner:

- 200 g/m²
- Chlorine free bleached Kraftliner
- FSC

SHELF LIFE AND CONDITIONS



- Recommended application temperature: min. + 5°C
- Product usage temperature: +20 °C
- Shelf life at 15/20°C/55% moisture: 9 months in original boxes

CERTIFICATES

Does NOT contain Phthalates in its plasticizers. Film produced according to European guidelines 2009/48/EC. Complies to: EN71-3-2005+A1-2007 re Monomers, Solvents, Plasticisers; to EN71-3:2019 Migration of certain elements-Category III and Appendix C Formaldehyde; to 2004/781EC and REACH (ECHA) updated to 14 June 2023. Use approved in children's games. Does not contain PFAS.

APPLICATIONS

- Short term indoor advertising
- Point of sale promotions
- Easy to apply

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

COALA FOLIO CLING



antalisTM

EMPOWERING
VISUAL
EMOTIONS