

MATERIAL DESCRIPTION

Coala Frontlit Daily S is a white semi-matt coated frontlit banner, available in 450g/m² and 510g/m².

PRINTER & INK COMPATIBILITY



WEIGHTS AVAILABLE



PRODUCT STRUCTURE

- Fabric:
 - High strength polyester
 - Base fabric: 1000 x 1000 denier
 - Construction: 18x18 weaving per inch
- Finish: White semi-matt
- Total weight: 450g/m²: Fabric 157g/m² + PVC 293g/m²
Thickness: 0,38mm
- Total weight 510g/m²: Fabric 157g/m² + PVC 353g/m²
Thickness: 0,42mm

CHARACTERISTICS

- 1 side printable
- Wind & print side: inside
- Tensile strength - DIN53352 BS3424
 - 450g/m²: 2000N/5cm (Warp) - 1800N/5cm (Weft)
 - 510g/m²: 2200N/5cm (Warp) - 1900N/5cm (Weft)
- Tear strength – DIN53356 BS3424
 - 450g/m²: 240N/5cm (Warp) - 200N/5cm (Weft)
 - 510g/m²: 250N/5cm (Warp) - 210N/5cm (Weft)
- Adhesion - DIN53357 BS3425 Method9B: 80N/5cm
- Temperature - DIN53357 BS3425 Method10:
-20°C / +70°C
- REACH compliant
- Flame retardant: this product does exist with flame retardant components and a B1 certification or without flame retardant components. Please refer to the item description.

APPLICATIONS

- Indoor & Outdoor Banners
- Pole banners
- Billboards
- Display systems

BENEFITS

- Very good printing quality
- Good weldability
- High tear resistance
- Good UV resistance



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

