

# COALA FRONTLIT EVENT 440 BANNER



## MATERIAL DESCRIPTION

Coala Frontlit Event 440 Banner is a white matt laminated frontlit banner.

## PRINTER & INK COMPATIBILITY



## WEIGHT



## PRODUCT STRUCTURE

- Polyester fabric – Din 600001 / DIN EN ISO 2060
  - 300x500 denier
  - 18x12 thread count per inch
- High strength polyester
- Type of coating: PVC
- Finish: White matt

## CHARACTERISTICS

- 1 side printable
- Wind & print side: inside
- Tensile strength - ISO 527/3:1995
  - 700N/5cm (L)
  - 650N/5cm (W)
- Tear strength - ISO 4674/3:2003
  - 80N/5cm (L)
  - 60N/5cm (W)
- Low temperature - ISO 13934-1:1999:  
30°C / -22°F
- RF Wealdable (Heat sealable) – DIN53354
- REACH compliant

## APPLICATIONS

- Indoor & short term outdoor Banners
- Display systems

## BENEFITS

- Good flexibility
- Brilliant color reproduction
- Good weldability

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

