

COALA FRONTLIT PRO 510FR BANNER



MATERIAL DESCRIPTION

Coala Frontlit Pro 510FR Banner is a white matt coated frontlit banner.

PRINTER & INK COMPATIBILITY



WEIGHT



PRODUCT STRUCTURE

- Polyester fabric – Din 600001 / DIN EN ISO 2060
 - 1000 x 1000 denier
 - 18 x 18 thread count per inch
- High strength polyester
- Type of coating: PVC
- Finish: White matt

CHARACTERISTICS

- 1 side printable
- Wind & print side: inside
- Tensile strength - ISO 527/3:1995
 - 1800N/5cm (L)
 - 1800N/5cm (W)
- Tear strength - ISO 4674/3:2003
 - 280N/5cm (L)
 - 250N/5cm (W)
- Adhesion strength – DIN 53357:1982
60N/5cm
- Low temperature - ISO 13934-1:1999
-30°C / -22°F
- RF Wealdable (Heat sealable) – DIN53354
- REACH compliant
- Flame retardant: B1 and M1

APPLICATIONS

- Indoor & Outdoor Banners
- Pole banners
- Billboards
- Display systems

BENEFITS

- Very good printing quality
- Good weldability
- High tear resistance
- Good UV resistance



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.



COALA FRONTLIT PRO 510FR BANNER



antalis^{EM}
Just ask Antalis