

MATERIAL DESCRIPTION

Coala Interior Film Leather Prestige is a hyper-realistic leather covering in adhesive version. With its high-end texture and thickness of 1050 µm, this innovative material will give character to your spaces with the ease of installation of an adhesive film. 10 exclusive colors, ranging from deep blue to soft pink tones, this range will bring luxury and originality to the renovation of walls, doors, and furniture.

GENERAL SPECIFICATIONS

- + Collection : Textile
- + Sub-category : Leather Prestige

- + Type of product : PVC
- + Adhesive : Acrylic PSA with air release system
- + Thickness : 1050 µm
- + Width : 122 cm
- + Length of roll : 10ML
- + Weight of a full roll of 10 ML = 30 KG
- + Finish : Matte
- + Not Stretchable

- + Sold by Linear Meter

- + Warranty 5 years
- + Resistance to scratch : Average
- + Storage (max 3 years from delivery) : 5° C - 30° C

- + Installation method : Dry
- + Installation area : Interior
- + Installation temperature 12° C - 38° C
- + Installation method : ABAB

CERTIFICATIONS

- + CE Wallcovering (EN15102) : Compliant
- + REACH : Compliant
- + Fire rating (EN13501-1) : M1 (NF P92- 507)
- + Dimensional stability (ISO 3759) :
24h at 50° C - 65% humidity = 0,25 mm



MAINTENANCE

For daily care, use a mild soap or pH-neutral detergent to clean the film's surface. Avoid using products with extremely acidic or basic pH levels, as they can harm the material. When cleaning the film surface, only use soft cloths or sponges to prevent any damage. For stubborn stains, apply hot water (not boiling) to the affected area. If necessary, use a solution of 70% isopropyl alcohol, 30% water for cleaning. For sanitizing, use only isopropyl alcohol-based products like Isopropyl Alcohol Wipes (not for daily use). Avoid organic-based cleaners like ammonia or polish, as they can damage vinyl. Test any cleaning detergents, bactericides, or virucidal products on a hidden area first to ensure compatibility. Use a brush with gentle bristles to clean. In case of wet or damp stains, use an absorbent cloth to wipe away the moisture and promptly and thoroughly dry the affected area. These recommendations will maintain the film's appearance and extend its lifespan. Persistent stains may indicate inadequate care, in which case, consider using a patch repair method (not guaranteed but effective and economical) or replacing the entire vinyl.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

