

MATERIAL DESCRIPTION

Coala PP Floor Lam is a 170 μ soft polypropylene matt textured lamination film for floor graphics. The structured surface of the film assures the anti-slip protection (R10). This product is a PVC free, plasticizer free, floor graphic solution if used in combination with Coala PP Stick. It is also great for Roll-Ups/Pop-Ups applications. This laminate can be used to protect UV printed media.

THICKNESS

170 μ

FEATURES

- Face Film: transparent PP film
- Face film thickness: 170 μ m
- Finish: matt
- Adhesive: pure polyacrylic, permanent, transparent
- Adhesive weight: 30g/m²
- Liner: Glassine Paper, white, 63 g/m²
- Total thickness: 0,2 mm

PRODUCT CHARACTERISTICS

- Adhesion on steel (after 24 h): 10 N / 25mm (AFERA 5001)
- Dimensional Stability MD: max 0.2mm (FTM 14)
- Dimensional Stability CD: max 0.2mm (FTM 14)

APPLICATIONS

- Cold lamination of floor graphic prints
- Lamination of Roll-Up and Pop-Up film

TEMPERATURE

- Application temperature: min. +10°C
- End-use temperature range:
from -40°C to +80°C

BENEFITS

- PVC Free
- Anti-slip rated R10



STORAGE



- Shelf life: 2 years, stored in the original packaging at +20 to +25°C and at 50% relative humidity
- Durability: 2 years

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

