

MATERIAL DESCRIPTION

Coala Quickstick W is a 350 mic self-adhesive semi-rigid PVC film with ultra low tack adhesive. Can be applied in a second even on uneven surfaces.

PRINTER & INK COMPATIBILITY



FILM THICKNESS

350
μ

PRODUCT DESCRIPTION

- **Carrier:**
 - Film: Coated rigid PVC film
 - Opacity: >99 %
 - Thickness: 350μ topcoated
 - Weight: 450 g/m²
- **Adhesive:**
 - Water based removable polyacrylate dispersion
- **Liner:**
 - PE-liner, 70μ siliconized
 - Weight: 70g/m²
- Adhesion (DIN 53357):
 - (24 h) N/25 mm: 12,5

ADDITIONAL INFORMATION

- Pasting temperatures: min. 15°C
- Temperature resistance: 80°C till -30°C

APPLICATIONS

- Temporary, quick and frequently display for indoor and outdoor areas
- Trade shows
- POS advertisements

BENEFITS

- Excellent flatness and stiffness
- High opacity
- Can be applied on smooth and slightly uneven surfaces
- Fast drying
- High tearing strength
- Low reflection surface
- Very easy to apply
- Its rigidity avoids any bubble issue
- Very easy to remove, Leaves no residue
- Prints great with waterbased Inks



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

SHELF LIFE STORAGE AND CONDITIONS



- In original packaging in a cool and dry environment at a room temperature of 10°C to 25°C and at a relative humidity of 35% to 65%.
- Processing : within one year after receipt.

