

MATERIAL DESCRIPTION

Coala Stickywall S is a PVC free, non-woven wallpaper (made of pulp and synthetic fibers) with a removable water based acrylic adhesive for easy application. Coala Sticky Wall S is water repellent and has a silk inkjet coating which provides excellent printing results for fine art reproduction.

PRINTER & INK COMPATIBILITY



THICKNESS

315 μ

WEIGHT

225
g/m²

ADVANTAGES

- Excellent printing results and fast drying of inks
- Very good wall and crack coverage
- Dimensionally stable

PROCESSING AND HANDLING

- Material should be acclimatized to room temperature
- The wall should be smooth, dry, grease free, preferably not painted, and last layer treated with a non-absorbing preparation primer.
- To avoid fingerprints, it is advisable to wear cotton gloves
- Before further processing of prints a minimum drying time of 24 hours is required
- If possible, always make trial tests for adhesive properties and if a compatibility with other substrates or ground surfaces exist
- Not suitable for latex printers

SHELF LIFE AND STORAGE CONDITIONS

- Processing: within one year after receipt
- Storage conditions: in original packaging, in a cool and dry environment
- Room temperature 10-25°C with 35-65% relative humidity

FEATURES

- Waterbased polyacrylate dispersion, semi-permanent
- Liner: One-side siliconised heavy paper

APPLICATIONS

- Exhibition stand
- Shop Wall decoration
- Individual wall decors for exhibitions, especially for trade shows and museums
- Photographic and art portraits
- Temporary application for indoor use

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.