










## MEDIATEX® Twintex FR

		Einheit Unit	Norm Standard	Wert Value
Substrat Substrate			DIN 60001	100% Polyester 100% polyester
Bindung Weave			DIN ISO 9354	Gewirke knitted fabric
Flächengewicht Weight		g/m <sup>2</sup>	DIN EN ISO 2286-2	400 ± 25
Brandverhalten Fire retardancy			DIN 4102 B1	ja yes
Tintenart Type of ink			UV LATEX	UV-härtende Tinten, Latextinten UV-curable inks, latex inks
Anwendung Application				innen indoor
Breite Width		cm inch	DIN EN ISO 2286-1	max. 310 max. 122
Druckseite Print side				beidseitig both-sided
Rollenlänge Roll length		m		30 - 50 ± 0,5

### Anwendungen Applications



Blockout / blackout  
Display / display  
Roll up / roll up  
Banner / banner  
Frontlit / frontlit  
Messebau / trade show graphic  
Rollo, Lamelle, Flächenvorhang /  
roller, vertical, panel blinds

### Besonderheiten Characteristics

- höchste Druckqualität  
highest print quality
- kein Weißbruch  
no white cracking / crazing
- kalt schneidbar  
trimming cold
- leichte Montage  
easy to mount
- doppelseitig bedruckbar  
printable on both sides