

NATURE WALK

NatureWalk is a vegan and recyclable film, which thanks to its specially designed surface and highly adaptable structure, reinvents the floor as an advertising, information or decorative surface. Its structure increases safety (R10) and allows incredible color explosions with any digital printer. The special surface structure has a very high mechanical abrasion resistance. The lightweight material adapts easily to the natural surfaces and can be installed easily and very quickly and removed without leaving any residue.

NatureWalk can be used indoors and is also convincing when used on walls and ceilings. It is flame retardant, dimensionally stable and very tear-resistant.

Durability

The durability depends on the way the product has been applied as well as on the condition of the surface and the amount and type of traffic on the area. We recommend a maximum 3 to 6 months use for indoor applications. Extended durability is possible when using a liquid laminate onto the printed area. Life time can be significantly extended with EasyProtect liquid vanish.

Printing method

UV, solvent, ecosolvent and latex

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

NatureWalk is designed to be fully recyclable.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warrantees of any kind are made to the accuracy of suitability for specification.

Uses

- Tiles, wooden and vinyl floors and untreated stone floors
- Wall graphics and door coverage
- · Tradeshows (exhibition walls and floors)
- POP/POS

Features & Benefit

- No or almost no adhesive residue
- Sticks on almost any surface
- Easy to apply and remove
- Print and go no lamination solution
- Digital cutting into any shape



| Technical Information NatureWa | | |
|--------------------------------|---------------------------------|---------------|
| Size | Width: 1.37 m Length: 30.48 m | |
| Material | Special coated polyester film | 180μ +/- 5μ |
| Adhesive | Permanent acrylic solvent | 80μ +/- 5μ |
| Certificates | Slip resistance | R10 |
| | Flame resistance / Flammability | B1 / M1 |
| Application | Minimum application temperature | +10°C / +50°F |