# **PRODUCT SPECIFICATION**



## Antique White Laid (IDP) Permanent



## **Description**

90gsm narrow ribbed laid paper with subtle 'antique' white colour. High wet strength, alkali resistant and mould proof. High quality label paper designed for bottle, jar and can labelling. Due to material stiffness use with care on small diameter applications.

### **Adhesive**

Aqueous acrylic emulsion adhesive. Minimum application temperature: +5°C Temperature range: -20°C to +80°C Chill grade - ideal for chilled food labelling. Designed for permanent 'wine bottle' labelling including bottles immersed in ice buckets or chillers. Very good heat resistance which enables trouble free performance in different hot fusing print processes. Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces. Good 'all round' permanent adhesive. Approved for indirect food contact. The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations. No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

## **Backing**

White high density kraft paper with excellent lay flat properties

## **Printing Information**

#### Litho:

Treat as a lic-coated paper. Die cut labels - use formulated extra low tack inks (not just reduced) and a hard blanket (compressibles are not advised as they increase the suction effect on the labels).

#### Laser & Copier - 'digital':

Excellent laser printing qualities. For best results set paper type as Plain and media weight appropriate to the laminate.

#### Ink Jet:

Not suitable for aqueous based ink jet

#### **HP Indigo:**

Approved for HP Indigo printing.

#### Laminate:

Thickness: 172 mic Weight: 190gsm

## **Availability**

Available in ranges:

**PCL** 

Digital Office

A4+

**A3** 

PCL3 Digital

SRA3+



Disclaimer: Technical information, statements and recommendations are given in Discalamer: Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Samples available on request. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.

This specification sheet replaces all earlier ones.

All information subject to change without notice.

© Label Connections Limited 2013. All rights reserved. www.pcllabels.com

Tel: +44 1480 211222 sales@labelconnections.co.uk