

PRODUCT SPECIFICATION



Machine Coated Gloss (IDP) Removable



Description

90gsm, white, woodfree machine coated gloss.

Adhesive

Aqueous acrylic emulsion removable adhesive.

Minimum application temperature: +5°C

Temperature range: -30°C to +80°C

A general purpose removable adhesive designed for safe use in hot fusing laser and copier printing.

Removable labels can be used as a deep freeze grade providing the labels are applied to dry goods at room temperature. Please be aware that removable adhesives can permanently bond to some substrates under certain conditions - please request trial sheets to assess suitability for a particular end use.

Approved for direct contact on dry and 'moist' non-fatty foods.

The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations.

No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

Backing

White high density kraft paper with excellent lay flat properties

Printing Information

Litho:

Treat as a coated paper.

Die cut labels - use formulated extra low tack inks (not just reduced) and a hard blanket (compressibles are not advised as they increase the suction effect on the labels). Be aware that due to the nature of removable adhesives the bond of the label to the backing is not as strong as permanent adhesives and extra care should be taken when litho printing pre cut labels.

Laser & Copier - 'digital':

Excellent laser printing qualities.

For best results set paper type as Plain or Coated Gloss and media weight appropriate to the laminate.

Ink Jet:

Not suitable for aqueous based ink jet

HP Indigo:

Approved for HP Indigo printing.

Laminate:

Thickness: 172mic Weight: 190gsm

Availability

Available in ranges:

PCL

Digital Office

A4+

A3

PCL3 Digital

SRA3+



Disclaimer: Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Samples available on request. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment. This specification sheet replaces all earlier ones. All information subject to change without notice.

© Label Connections Limited 2013. All rights reserved.
www.pcllabels.com

Tel: +44 1480 211222
sales@labelconnections.co.uk

File date: 05/2013