

## The art of contrast

Print Speed offset is a range of premium uncoated papers, which has become the benchmark reference in uncoated papers for more than 20 years. It provides a unique combination of premium whiteness, bulk and opacity to enhance the visual and tactile features of your printing documents.



## **Product features:**

- + An optimized high whiteness
- + Smooth paper surface
- + Reliable performance & runability



## **Applications:**

- Print Speed offset is designed for offset printing, providing consistent machine performance and excellent printing results.
- It is suitable for printing brochures, folders, flyers, desk calendars, note book covers, business reports, newsletters and mailings.
- A wide range of professional papers available in multiple formats and weights.

Basis weight (g/m2)	ISO 536	70	75	80	90	100	120	135	150	170	190	217	250	300	350
Whiteness (CIE)	ISO 11475	161	161	161	161	161	161	161	161	161	161	161	161	161	161
Brightness (%)	ISO 2470-2	110	110	110	110	110	110	110	110	110	110	110	110	110	110
Caliper (µm)	ISO 534	92	95	106	116	128	150	158	175	196	222	254	295	365	425
Roughness (ml/min)	ISO 8791-2	150	180	150	150	150	150	130	130	140	150	150	180	200	200
Stiffness MD, mN	ISO 2493-1	<u>&gt;</u> 70	<u>&gt;</u> 90	<u>&gt;</u> 100	<u>&gt;</u> 130	<u>&gt;</u> 180	<u>&gt;</u> 260	<u>&gt;</u> 340	<u>&gt;</u> 475	<u>&gt;</u> 680	<u>&gt;</u> 865	<u>&gt;</u> 1120	<u>&gt;</u> 1550	<u>&gt;</u> 2600	<u>&gt;</u> 3700
Stiffness CD, mN	ISO 2493-1	> 25	> 30	> 35	> 50	> 70	> 110	> 225	> 320	> 460	> 580	> 750	> 1090	> 1430	> 2000
Opacity (%)	ISO 2471	91	92	94	95	96	98	98	99	99	100	100	100	100	100
Moisture (%)	ISO 287	6,2	6,2	6	6	6	5,8	6,5	6,5	6,5	6,5	6,5	6,5	6,5	6,5

























06.08.2025

