

Print Speed® laser-jet



- Bright superior whiteness for a perfect reproduction of colours
- Exceptional bulk level and opacity thanks to its Eucalyptus Globulus fibre content
- A uniform surface with an excellent smoothness for optimum high-quality printability
- A natural touch & feel, ideal to give another dimension to all your day-to-day applications
- Environmentally friendly : ECF pulp, Green Star System with 4 stars, FSC® and European Ecolabel certifications



Print Speed® laser-jet

Basis weight (g/m2)	ISO 536	75	80	90	100	120	135	160	200	250	300
Brightness (%)	ISO 2470	112	112	112	112	112	114	114	114	114	114
Whiteness (CIE)	ISO 11457	169	169	169	169	169	170	170	170	170	170
Roughness (ml/min)	ISO 8791-2	200	150	150	100	50	140	140	140	140	140
Opacity (%)	ISO 2471	93	95	96	97	98	97	97.5	99	99	99
Moisture (%)	ISO 287	5.2	5.2	5.2	5.2	5.2	4.8	4.8	5.5	5.5	5.5
Bulk (cm3/g)		1.37	1.35	1.28	1.18	1.05	1.26	1.26	1.30	1.30	1.30
Caliper (µm)	ISO 534	103	108	115	118	126	173	202	260	325	390

These values are to be considered only as indications and are subject to change according to trade tolerances in the quality specification
Issue Date: September 2016



Discover all the Print Speed range at www.antalis.fr