

UPM Raflatac Technical Information

11.09.2012 ENG 568

SELF-ADHESIVE	SHEETS
FACE	RAFLACOAT PLUS FMC
Gloss Coated	BUK (sales code)
Product	White woodfree machine coated midgloss paper.
Use	Universal label paper for quality multicolour labels requiring high contrast and fine printing detail.

Typical technical values

Substance	80	g/m ²	ISO 536	
Caliper	70	µm	ISO 534	
Tensile strength MD	5.8	kN/m	ISO 1924/1	
Tensile strength CD	2.8	kN/m	ISO 1924/1	
Brightness	90	%	ISO 2470/1	
Roughness	1.0	µm	ISO 8791	PPS 10
Opacity	89	%	ISO 2471	
Gloss	64	%	Hunter 75°	
CIE Whiteness	120	%	ISO 11475	
Stiffness MD	0.23	mNm	ISO/DP 2493	
Stiffness CD	0.13	mNm	ISO/DP 2493	
Printability	Flexography, letterpress, offset, rotogravure and screen. Hot foil. Suitable for thermal transfer printing with wax/resin ribbons. Testing recommended.			
Advantages	This new medium stiffness paper is stronger and more rigid than ever providing faster conversion speeds. Provides high degree of print contrast and high opacity.			
Sustainability	Products named as FMC are registered to SGS-COC-004879 FSC™ mix credit.			
Warranty	Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. This publication replaces all previous versions. All information is subject to change without notice.			



UPM

www.upmraflatac.com