

6792



Product description

TransferRite® 6792 is a high tack application tape featuring a premium, moisture resistant saturated paper backing with specially formulated latex, pressure sensitive adhesive.

Applications

Can be used in sign shops for very small lettering, fine line striping and can also be used in screen printing. 6792 is ideal for applications where superior dimensional stability, humidity resistance, or long term storage stability is required.

Technical information

Paper thickness (without adhesive)	111 µm
Adhesive thickness	24 µm
Total thickness	135 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	4.4 N/25mm (high tack)
Core colour	red
Tensile strength	92 N/25mm
Elongation at break	14%
Shelf life (from time of manufacture)	30 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

