

DATA SHEET – XEROX DURAPAPER LABEL

Description:-

- Self adhesive label made of polyethylene film.
- Extremely robust, suitable for harsh & outdoor conditions
- Face material white, matt, opaque polyethylene film, highly filled with non-abrasive silicates.
- Adhesive solvent free, UV-cured acrylic based adhesive, permanent, transparent.
- Release liner white kraft, using chlorine free pulp.
- Combination of strong yet conformable synthetic face material and aggressive adhesive means it will adhere and stay on most surfaces, smooth or rough, flat or slightly curved, in most conditions.
- BS5609 certified – chemical drum labelling approved.
- Water resistant
- Weather resistant



Compatibility:-

- Suitable for most dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines. Best printed as heavyweight media. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Properties:-

Material	Property	Value
Face	Grammage gsm (ISO 536)	116
Face	Caliper mic (ISO 534)	178
Release Liner	Grammage gsm (ISO 536)	93
Release Liner	Caliper mic (ISO 534)	86
Adhesive	Tack	extremely high
Adhesive	Peel Adhesion	extremely high
Adhesive	Shear	extremely high
Adhesive	Min Application Temp	0 °C
Adhesive	Service temperature	-40 to +150 °C
Total Laminate	Grammage gsm (ISO 536)	219
Total Laminate	Caliper mic (ISO 534)	258

Xerox Part No.	Sheet size	Labels/sheet
003R98688	SRA3	1
003R97344	A4	1
003R98645	A3	1



Discover all the Xerox Speciality Media Range at
www.antalıs.com

