

# DATA SHEET – XEROX FLOOR GRAPHIX

## Description:-

- An indoor Floor Graphic material from Xerox, designed for dry toner laser printers.
- Print and apply. No lamination required.
- Slip rating approved - R10 certification.
- Made from polyester, hence no shrinkage
- Durable and scuff resistant
- Easy to apply and remove
- Works on hard surfaces and short-pile carpets
- Not suitable for outdoor environments

## Compatibility:-

- For dry toner digital presses.
- Need to have capability to print 350g media
- Printer speed ratings typically 50 pages/min +
- Run on heavyweight paper settings
- For printers which have them, use bypass trays (for straightest path through printer) or hi capacity trays.
- Where available, use image quality adjustment systems to optimise print quality e.g.. Xerox SIQA system
- Output to top trays.

## Properties:-



Material	Property	Value
Face	Grammage gsm (ISO 536)	195
Face	Caliper mic (ISO 534)	153
Release Liner	Grammage gsm (ISO 536)	130
Release Liner	Caliper mic (ISO 534)	120
Adhesive	Thickness	27 +/- 5
Adhesive	Peel Adhesion N/25mm	8.5 +/- 1.5
Adhesive	Shear	extremely high
Adhesive	Application temperature	+5 to +50 °C
Adhesive	Service temperature	-40 to +180 °C
Total Laminate	Grammage gsm (ISO 536)	346 +/- 8
Total Laminate	Caliper mic (ISO 534)	300 +/- 6

Xerox Part No.	Sheet size	Labels/sheet
003R90319	SRA3	50
003R90320	SRA3	250



Discover all the Xerox Speciality Media Range at [www.antalisis.com](http://www.antalisis.com)

