

FILM BULLE ANTISTATIQUE

Item codes Antalis

400798

06 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	Film bulle antistatique
MATERIAL	- Polyethylene - Rose - Boîte de 1 rouleau
ADVANTAGES	- Matériau de rembourrage léger et sûr - Qualité antistatique - Reconnaissable à sa couleur rose
APPLICATION AREAS	Protection anti-choc des produits type câblage, pieces détachées, informatique

FILM BULLE ANTISTATIQUE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Mousse polyethylene	-
Couleur	-	Rose	-
Dimensions	-	1000x100	Mm x m
Durée de vie (typique)	-	12	Mois
Hauteur des bulles	-	4.5	mm
Diametre des bulles	-	12	mm
Nombre de bulles au m ²	-	6600	Bulles/m ²
Grammage	-	58	g/m ²
Epaisseur	-	64	µm
Resistance à la traction Longitudinale	-	40	N/m
Resistance à la traction transversale	-	20	N/m
Resistance à la perforation	-	13	N

EXPLANATION VALUES USED IN TABLE

All above values are typical values at conditioning atmosphere XX% and XX°C according to ISO-standards.

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.