

## PAPIER KRAFT D'EMBALLAGE BRUN

Item codes Antalis

364925

30 / 10 / 2023



### CHARACTERISTICS

|                   |                                                                                                                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DESCRIPTION       | <ul style="list-style-type: none"> <li>Papier kraft Adour naturel Brun</li> </ul>                                                                                                                                                     |
| MATERIAL          | <ul style="list-style-type: none"> <li>Papier kraft, Brun</li> <li>Papier à base de fibres vierges</li> <li>Vendu par rouleau</li> </ul>                                                                                              |
| ADVANTAGES        | <ul style="list-style-type: none"> <li>Papier réutilisable, recyclage et biodégradable</li> <li>Resistance élevée à l'éclatement, la déchirure et l'humidité</li> <li>100 % naturel, en pâte de fibres de bois de résineux</li> </ul> |
| APPLICATION AREAS | <ul style="list-style-type: none"> <li>Emballage pour livres et imprimées, emballage de protection, intercalaire, bourrage, calage</li> </ul>                                                                                         |

## PAPIER KRAFT D'EMBALLAGE BRUN

### TECHNICAL DATA

| SPECIFICATION           | STANDARD | VALUE                           | UNIT             |
|-------------------------|----------|---------------------------------|------------------|
| Matière                 | -        | Papier kraft                    | -                |
| Composition             | -        | Papier à base de fibres de bois | -                |
| Dimensions              | -        | 650 x 310                       | mm/m             |
| Grammage                | -        | 70                              | g/m <sup>2</sup> |
| Absorption eau Cobb 60s | -        | 30                              | g/m <sup>2</sup> |
| Indice éclatement       | -        | 4.5                             | mini kPa.m/g     |
| Force à la rupture      | -        | 100<br>35                       | mini SM<br>ST    |
| Humidité                | -        | 6.5                             | moy %            |

#### EXPLANATION VALUES USED IN TABLE

All above values are typical values at conditioning atmosphere XX% and XX°C according to ISO-standards.

- ISO 536
- ISO 2758
- ISO 1924
- ISO 287
- ISO 535

#### REGARDING TOLERANCES

All Technical data provided are average values.  
Very slight variations are possible due to material tolerances.  
We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.