

	Ref. STD	Unit of meas.	TECHNICAL SPECIFICATIONS			
Substance	ISO 536	g/m ²	120	250	320	
Caliper	ISO 534	µm	125	290	370	
Bulk	ISO 534	cm ³ /g	1,04	1,16	1,16	
Smoothness Bekk	ISO 5627	s	70	50	50	
Gloss Gardner	ISO 8254-1	%	26	24	24	
Brightness ISO	ISO 2470 (D65)	%	92	92	92	
Opacity ISO	ISO 2471	%	95	98	99	
Stiffness L&W 15 degrees MD	ISO 2493	mN	30	100	180	
Stiffness L&W 15 degrees CD	ISO 2493	mN	15	40	90	

Tolerances	Ref. STD	Unit of meas.	RANGE			
Substance	ISO 536	g/m ²	115/125	240/260	308/332	
Caliper	ISO 534	µm	119/131	275/305	352/388	
Bulk	ISO 534	cm ³ /g	-	-	-	
Smoothness Bekk	ISO 5627	s	49/91	35/65	35/65	
Gloss Gardner	ISO 8254-1	%	22/30	20/28	20/28	
Brightness ISO	ISO 2470 (D65)	%	90/94	90/94	90/94	
Opacity ISO	ISO 2471	%	93/97	96/100	97/101	
Stiffness L&W 15 degrees MD	ISO 2493	mN	26/35	85/115	150/210	
Stiffness L&W 15 degrees CD	ISO 2493	mN	13/17	34/46	76/104	

Notes: CARTA IGNIFUGA
 Finishing
 Printing method **Sheet-fed offset**
 Applications

Values referred to each quality are to be considered as reference data and could change without notice. Each value is subject to trade tolerances.