

PAPIER KRAFT ADOUR NATUREL

Item codes Antalis

306309

09 / 2023



CHARACTERISTICS

DESCRIPTION	Papier Kraft Adour naturel
MATERIAL	- Kraft Adour naturel - Blond - Grammage: 90 g / m² - Dimensions: 640 mm x 450 mm
ADVANTAGES	- Certifié 100 % PEFC - Papier recycle, réutilisable et recyclable, certifié PEFC - Excellente résistance à la déchirure - Aspect esthétique pour valoriser vos produits
APPLICATION AREAS	- Pour l’emballage et la protection de vos produits - Pour le calage et le remplissage de vide de vos colis - Utilisation en intercalaire de palettisation

PAPIER KRAFT ADOUR NATUREL

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Epaisseur	-	113	μm
Volume massique	-	1.26	cm3/g
Absorption eau COBB 60R°	-	27	g/m²
Resistance à la traction SM	-	6.45	kN/m
Resistance à la traction ST	-	3.36	kN/m
Longueur de rupture SM	-	7300	m
Longueur de rupture ST	-	3800	m
Resistance à l'éclatement	-	279	kPa
Humidité Moyenne	-	7.7	%

EXPLANATION VALUES USED IN TABLE

All above values are typical values at conditioning atmosphere XX% and XX°C according to ISO-standards.

- ISO 536
- ISO 534
- ISO 5636/3

REGARDING TOLERANCES

All Technical data provided are average values.
Very slight variations are possible due to material tolerances.
We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.