

FILM PRE-ETIRE MACHINE

Item codes Antalis

437174

19 / 09 / 2024



CHARACTERISTICS

DESCRIPTION	Film pré-étiré machine
MATERIAL	- Polyéthylène transparent - Cast - Palette de 26 bobines
ADVANTAGES	- Économique - Performant : préétiré de façon optimale - Qualité du filmage constante - Recyclable
APPLICATION AREAS	Filmage de palette

FILM PRE-ETIRE MACHINE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyéthylène (cast)	-
Couleur	-	Transparent	-
Largeur	-	430	+/-2% mm
Longueur	-	2600	+/-2% m
Poids brut	-	9.8	+/-10% kg
Poids net	-	8.23	+/-10% kg
Epaisseur	-	0.008	+/-0.001 mm
Tension	ASTM D 882	MD : 16.6 TD : 8	+/-10% N/mm ²
Résistance à la traction	-	MD : 127 TD : 43	+/-10% N/mm ²
Allongement à la rupture	EN ISO 9001	MD : 125 TD : 860	+/-50 %

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.