

## RUBAN DE TOILE ADHESIVE

Item codes Antalis

401118

04 / 12 / 2023



### CHARACTERISTICS

|              |                                                                                                                                                                                                                    |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DESCRIPTION  | <ul style="list-style-type: none"> <li>Ruban de toile adhesive polyethylene gris</li> </ul>                                                                                                                        |
| MATERIAL     | <ul style="list-style-type: none"> <li>Polyethylene, hotmelt</li> <li>Gris</li> <li>Boîte de 24 rouleaux</li> </ul>                                                                                                |
| ADVANTAGES   | <ul style="list-style-type: none"> <li>Usage multiple</li> <li>Se déchire facilement</li> <li>Forte adhésion instantanée</li> <li>Tack important qui permet de l'utiliser pour le maintien des films PE</li> </ul> |
| APPLICATIONS | <ul style="list-style-type: none"> <li>Utilisée notamment lors de désamiantage, elle sert au raccord de gaine de ventilation ou de climatisation</li> </ul>                                                        |

## RUBAN DE TOILE ADHESIVE

### TECHNICAL DATA

| SPECIFICATION               | STANDARD | VALUE                                 | UNIT   |
|-----------------------------|----------|---------------------------------------|--------|
| Support                     | -        | Film LDPE + fibre polyester           | -      |
| Masse adhésive              | -        | Sans solvant / caoutchouc synthétique | -      |
| Couleur                     | -        | Gris                                  | -      |
| Dimensions                  | -        | 50 x 50                               | mm x m |
| Densité de fibre (maille)   | -        | 26                                    | -      |
| Épaisseur totale            | -        | 175                                   | µm     |
| Pouvoir adhésif sur l'acier | -        | 23                                    | N/25mm |
| Test de la bille d'acier    | -        | 3                                     | Cm     |
| Résistance à la traction    | -        | 95                                    | N/cm   |
| Tenue en température        | -        | -10 à 75                              | °C     |

#### REGARDING TOLERANCES

All Technical data provided are average values.  
 Very slight variations are possible due to material tolerances.  
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.