

FILM RETRACTABLE POLYOLEFINE SOUFFLE

Item codes Antalis

449667

08 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	Film retractable Polyolefine
MATERIAL	- Polyethylene - Transparent - Boîte de 1 rouleau
ADVANTAGES	- Très haute resistance - Excellente transparence et brillance - Utilisable sur tous types de machines (soudeuses à cloche ou à tunnel) - Aucun dégagement de chlore lors de la coupe soudure
APPLICATION AREAS	Emballage de produits alimentaires ou industriels

FILM RETRACTABLE POLYOLEFINE SOUFFLE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyethylene	-
Couleur	-	Transparent	-
Largeur	-	450	mm
Longueur	-	1000	m
Epaisseur	-	19	µm
Diametre du mandrin	-	76	mm
Densité	-	1.32	g/cm3
Tolerance	-	+/- 5	%
Temperature de retraction entre	-	80 120	°C
Taux de plastification	-	20	%

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.