

FILM ETIRABLE MACHINE STANDARD TRANSPARENT

Item codes Antalis

527980

24/10/2023



CHARACTERISTICS

DESCRIPTION	<ul style="list-style-type: none"> • Film étirable machine • Cast, étirabilité 160%
MATERIAL	<ul style="list-style-type: none"> • Polyéthylène • Transparent
ADVANTAGES	<ul style="list-style-type: none"> • Réduction de plastique sur la palette, réduction des déchets • Grande résistance du film à la déchirure • Accroissement de la stabilisation de la palette • Réduction du coût de la palette
APPLICATION AREAS	<ul style="list-style-type: none"> • Filmage, maintien et sécurisation des palettes

FILM ETIRABLE MACHINE STANDARD TRANSPARENT

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyethylene	-
Poids brut	-	11.8	(dont 1kg de mandrin) kg
Resistance à la traction	-	23.9	Tolerance 10% N/mm²
Allongement à la rupture	-	303	Tolerance 10% %
Largeur du film	-	485	2% mm
Étirabilité	-	160	- %

EXPLANATION VALUES USED IN TABLE

All above values are typical values at conditioning atmosphere XX% and XX°C according to ISO-standards.

REGARDING TOLERANCES

All Technical data provided are average values.
Very slight variations are possible due to material tolerances.
We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.