

FILM ETIRABLE POUR PRE-ETIRAGE MOTORISE

Item codes Antalis

527982

08 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	<ul style="list-style-type: none"> Film étirable machine cast
MATERIAL	<ul style="list-style-type: none"> Polyethylene Renforcé par des fibres Palette de 46 bobines
ADVANTAGES	<ul style="list-style-type: none"> Reduction de plastique sur la palette, reduction des déchets Grande resistance du film à la déchirure Accroissement de la stabilisation de la palette Résuction du coût de la palette
APPLICATION AREAS	<ul style="list-style-type: none"> filmage, maintien et sécurisation des palettes

FILM ETIRABLE POUR PRE-ETIRAGE MOTORISE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyethylene	-
Couleur	-	Transparent	-
Epaisseur	-	12	+/-1 µm
Laize	-	485	+/-2% mm
Longueur	-	2100	- m
Étirabilité	-	260	- %
Resistance à la rupture	-	25.5	+/-10% N/mm ²
Allongement à la rupture	-	375	+/-10 %
Diamètre mandrin	-	76	- Mm
Poids brute	-	11.9	- kg

REGARDING TOLERANCES

All Technical data provided are average values.
Very slight variations are possible due to material tolerances.
We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.