

FILM ETIRABLE MACHINE RENFORCE

Item codes Antalis

527982

08 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	Film étirable machine cast
MATERIAL	- Polyethylene - Renforcé par des fibres - Palette de 46 bobines
ADVANTAGES	- Reduction de plastique sur la palette, reduction des déchets - Grande resistance du film à la déchirure - Accroissement de la stabilisation de la palette - Reduction du coût de la palette
APPLICATION AREAS	Filage, maintien et sécurisation des palettes

FILM ETIRABLE MACHINE RENFORCE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyethylene	-
Couleur	-	Transparent	-
Laize	-	485	+/-2% mm
Longueur	-	2100	- m
Étirabilité	-	260	- %
Resistance à la rupture	-	23.5	+/-10% N/mm ²
Allongement à la rupture	-	375	+/-10 %
Diamètre mandrin	-	76	- mm
Poids mandrin	-	1.7	- kg
Poids brute	-	12.6	- kg

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.