

FILM ETIRABLE EN BOBINOT

Item codes Antalis

433164

19 / 09 / 2024



CHARACTERISTICS

DESCRIPTION	Film étirable manuel en Bobinot
MATERIAL	- Polyéthylène transparent, cast - Collant interne - Boîte de 44 rouleaux
ADVANTAGES	- Poignée incluse - Maniable - Pratique - Résistant
APPLICATION AREAS	Idéal pour le fardelage et le bottelage de petits colisages

FILM ETIRABLE EN BOBINOT

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyéthylène (cast)	-
Couleur	-	Transparent	-
Laize	-	100	+/-2% mm
Longueur	-	150	+/-2% m
Epaisseur	-	23	- μ
Charge à la rupture	ASTM D 882	Sens long : 32 Sens travers : 20	+/-10% N/mm ²
Résistance admissible	ASTM D 882	Sens long : 7.2 Sens travers : 7	+/-10% N/mm ²
Allongement à la rupture	ASTM D 882	Sens long : 520 Sens travers : 740	+/-10% %
Allongement mis en oeuvre	-	160	+/-10% %

REGARDING TOLERANCES

All Technical data provided are average values.
Very slight variations are possible due to material tolerances.
We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.