AHLSTROM

WALLSTAR DIGITAL SPRAY&UP

SPRAY & UP Matt 150

MA8009SU D 150

Technical Data Sheet

Revision 02 - Valid until : September 2024

High quality uncoated nonwoven for digital printing

Surface aspect:
Matt

Printing process:
UV / Latex

Printer benefits

- High dimensional stability
- Good opacity
- Excellent printability

End-user benefits

- Pre-pasted
- PVC-free and eco-friendly
- Luxurious, textile-like touch
- 100% paste-the-wall and strippable

Physical properties		
Grammage	150	g/m^2
Thickness	270	µm
Dry Tensile Strength MD	5 900	N/m
Dry Tensile Strength CD	3 900	*N/m*
Elongation MD	6.5	%
Elongation CD	14.0	%
Ratio Wet/Dry	39.0	%
Brightness	85.5	%
Opacity	90.0	%
Wet Stability CD (Maxi)	0.25	%
Side to be printed	Top Side	

Certification
Euroclass B-s1-d0

Certified for HP Latex Inks

FSC www.fsc.org
(on request)

Contact office:
Ahlstrom Brignoud
53 Rue Alfred Fredet
38190 Brignoud - France
Tel: +33 4 76 45 35 15
Fax: +33 4 76 71 27 20

www.ahlstrom.com

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom deems appropriate. Refer to www.ahlstrom.com for contact information.

Revised Tuesday, August 29, 2023